

Declaration of performance (DOP)



Mondo 30-CPR-2021/10/19-V1

Product type	Freestanding stove
Type	Mondo 30, Mondo 30 S, Mondo 30M
Serial Number	See EN-label
Intended use of the product	Room heater, without hot water supply
Fuel	Solid fuel
Manufacturer	Lotus Heating Systems A/S
Address of the manufacturer	Agertoften 6 5550 Langeskov DK
System of assessment and verification of constancy of performance of the product. AVCP	System 3
Harmonized technical specification	EN 13 240 : 2001/A2:2004/AC:2007
Notified Laboratory	Reihn-Ruhr Feuerstätten Prüfstelle, 1625 Test report: RRF-40 20 5639

Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 WT	
Distance to combustible materials	Minimum distance rear: 180/100mm Sides: 250mm Front: 1150mm	
Risk of burning fuel falling out	Pass	
Emission of combustion products	CO: 0.07 % CO: 875 mg/Nm ³ Dust: 17 mg/Nm ³ Dust NS: 3,68 g/kg dried wood OGC: 68 mg/Nm ³ NOx: 114 mg/Nm ³	EN 13 240: 2001/A2:2004/AC:2007
Surface temperature	Pass	
Cleanability	Pass	
Mechanical resistance(carry a flue)	Pass	
Risk of fuel falling out	Pass	
Nominal heat output	5,9 KW	
Energy efficiency	80 %	
Flue gas temperature at nominal heat output	274 °C	

Signed for and on behalf of the manufacturer by.

Lars U. Borch, CEO / Managing Director Lotus Heating Systems A/S

